

LRV/Metro Araçlar için 1500V/750V DC 600 kW Yüksek Frekans Anahtarlama DC/DC Konvertör

1500V to 750V DC

600 kW High Frequency Switching DC/DC

Converter for LRV/Metro



Özellikler | Features

- Giriş Voltajı: 1500V DC Nominal (+25%, -30%)
- Çıkış Gerilimi - Gücü: 750 VDC / 5x120 kW= 600 kW
- İzolasyon: Yes, Galvanically
- Kontrol Gerilimi: From 24 VDC to 110 V DC
- Koruma Sınıfı: IP65
- Çalışma Sıcaklığı: -25 °C / +45 °C
- Ağırlık: 150 kg for 120 kW module
- Ölçüler: 1300 x 650 x 395 mm
- Uygulama: Paralellenmiş 5 Ünite - Her biri 120 KW
- Input Voltage: 1500V DC Nominal (+25%, -30%)
- Output Voltage - Power: 750 VDC / 5x120 kW= 600 kW
- Isolation: Yes, Galvanically
- Control Voltage: From 24 VDC to 110 V DC
- Safety Class: IP65
- Working Temperature: -25 °C / +45 °C
- Weight: 150 kg for 120 kW module
- Dimensions: 1300 x 650 x 395 mm
- Application: Paralled 5 unit - each one of that is 120 kW

Çıkış voltajı ve çıkış gerilimi projeye göre tasarlanabilir ve değiştirilebilir.

Output voltage and output power could be designed and changed according to project.

from 60kW to 600 kW

